



**Type designation:**..... 2006  
**Designation IEC:**..... R6P  
**System:**..... Carbon Zinc  
**Shelf Life (coding)\*:**..... 36 months  
**Nominal Voltage [V]:**..... 1.5  
**Typical Capacity C [mAh]:**..... 1000 (discharge with high resistance)  
**Permissible Temperature Range:** -10 °C ..... 50 °C  
**Weight, approx. [g]:**..... 16.6  
**Volume [ccm]:**..... 7.6

Dimensions [mm]	min:	max:
∅	13.7	14.5
A	-	50.5
B	49.5	-
C	7.0	-
E	-	0.5
F	-	5.5
G	1.0	-



Discharge Type	Load	End Voltage[V]	0.9
4M/H,8H/D,7D/W Portable Lighting (LED)	3.9 Ω	Time [min]	125
Discharge Type	Load	End Voltage[V]	0.8
1H/D,7D/W Motor / Toys	3.9 Ω	Time [h]	1.8
Discharge Type	Load	End Voltage[V]	0.9
1H/D,7D/W CD / digital audio / wireless gaming and accessories	100 mA	Time [h]	7.2
Discharge Type	Load	End Voltage[V]	1.0
1H/8H,24H/D Radio / Clock / Remote Control	50 mA	Time [h]	16.2

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**

\*In consideration of typical loss of capacity at storage and application.